

## Specifications Table for 4MXM-A

					4MXM68A2V1B	4MXM80A2V1B
Dimensions	Unit	Height	mm		734	734
			Width	mm	974	974
			Depth	mm	408	408
Weight	Unit		kg	63	67	
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor
Operation range	Cooling	Ambient	Min.	°CDB	-10	-10
			Max.	°CDB	46	46
Sound pressure level	Cooling		Nom.	dBA	48	48
	Heating		Nom.	dBA	49	49
Refrigerant	Type				R-32	R-32
	Charge			kg	2.00	2.40
	Charge			TCO2Eq	1.35	1.62
	GWP				675	675
Piping connections	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 30m)	0.02 (for piping length exceeding 30m)
	Level difference	IU - OU	Max.	m	15	15
		IU - IU	Max.	m	7.5	7.5
	Total piping length	System	Actual	m	60	70
Standard Accessories	Installation manual				1	1
	Screw bag				1	1
	Drain plug				1	1
	Reducer assembly				1	1
	Drain cap (1)				6	6
	Drain cap (2)				3	3
Power supply	Phase				1~	1~
	Frequency			Hz	50	50
	Voltage			V	220-240	220-240
Notes					(1) - For one room	(1) - For one room
					(3) - See separate drawing for operation range	(3) - See separate drawing for operation range
					(4) - See separate drawing for electrical data	(4) - See separate drawing for electrical data
					(5) - Contains fluorinated greenhouse gases	(5) - Contains fluorinated greenhouse gases